

Cleavers

CI-01

- Economical Price
- Compact Design



CI-02

- Stable and long life cycle through double slide bearing system.
- Single action cleave system with fiber chip collector.



CI-06



CATEGORY	CI-01	CI-02
Fiber Diameter	125 μ m	125 μ m
Coating Diameter	250 ~ 900 μ m	250 ~ 900 μ m
Cleave Angle	90° \pm 0.5°	90° \pm 0.5°
Cleave Length	Single 5mm to 16 mm (coated fiber \leq 250 μ m) Single 10mm ~ 16mm, Ribbon 10mm (CI-02)	
Blade Life time	50,000	50,000
Dimension	58x55x48mm	84x65x54mm
Weight	340g	420g

CATEGORY	CI-06
Cleave Angle	90° \pm 0.5°
Cleave Life	2,000
Dimension	19x32x124mm
Weight	70g

* Remark: 5mm cleaving can only be for 250 μ m.

CI-03A

- Single Action for Cleaving (Full Automatic)
- Oil Damper System



CI-03B

- Single Action(Full Automatic) for cleaving & collecting fiber chips
- Oil Damper System



CATEGORY	CI-03A	CI-03B
Fiber Diameter	125 μ m	125 μ m
Coating Diameter	250 ~ 900 μ m	250 ~ 900 μ m
Cleave Angle	90° \pm 0.5°	90° \pm 0.5°
Cleave Length	Single 5mm to 16 mm (coated fiber \leq 250 μ m) Single 10mm ~ 16mm, Ribbon 10mm	
Blade Life time	50,000	50,000
Dimension	58x55x48mm	88x55x48mm
Weight	340g	400g

CI-08

- Typical Cleaving Angle Deviation: 6° ~ 9°
- Just one touch for tension, twisting, cleaving



CATEGORY	CI-08
Fiber Diameter	125 μ m
Coating Diameter	250 ~ 900 μ m
Cleave Length	6°~ 9°
Blade Life time	Max. 30,000
Dimension	104x72x56mm
Weight	400g

* Remark: 5mm cleaving can only be for 250 μ m.